



**Conformance Test Report  
for EN301 406 v1.5.1 (2003-07)  
Digital Enhanced Cordless Telecommunic. (DECT);  
Harmonized EN for Digital Enhanced Cordless  
Telecommunications(DECT) covering essential  
requirements under article 3.2 of R&TTE Directive;  
Generic radio**

**Report No.: 60.860.8.008.01**

Client:	SunCorp Communications Limited
Product:	DECT Phone
System Under Test (SUT):	DECT20-B14-RF19 (FP)
Manufacturer	Shenzhen Guo Wei Electronics Co., Ltd.
Date test item received:	2008/01/14
Date test campaign completed	2008/02/05
Date of issue:	2008/03/13
Test results:	COMPLIED

*The test report include test result of conformance log layer 1.*

*Total number of pages of this test report: 27 pages*

**The test result only corresponds to the tested sample. It is not permitted to copy this report, in part or in full, without the permission of the test laboratory.**

Approved by

A handwritten signature in blue ink, appearing to read 'Jeff Pong'.

Jeff Pong  
Deputy Telecom Manager

**TÜV SÜD Hong Kong Ltd.  
TÜV SÜD Group  
Unit 601 InnoCentre, 72 Tat Chee Avenue, Kowloon Tong, Kowloon**

## Contents

### **1 General**

1.1 Reason for measurements and identification of the protocol	3
1.1.1 Global statement of conformance	3
1.2 Identification and functional description of the test candidate	3
1.2.1 Client identification	3
1.2.2 Identification of the Test Candidate	4
1.2.3 Functional description	4
1.3 Climatic Conditions	5
1.4 Measurement accuracy	5
1.5 Test equipment used	5
1.6 Explanation of the results abbreviations	5
1.7 Comments for testing	6

### **2 IUT conformance status according to EN301 406 V1.5.1 (2003-07)**

2.1 IUT conformance summary	7
2.2 EN301 406 V1.5.1(2003-07) results overview	8
2.3 Test campaign repor	9
2.3.1 TC1 Accuracy and stability of RF carriers(4.5.1)	9
2.3.2 TC2 Timing jitter: slot-slot on the same channel(4.5.2)	9
2.3.3 TC3 Reference timing accuracy of a RFP	9
2.3.4 TC4 Measurement of Packet timing accuracy	9
2.3.5 TC5 Transmission Burst(4.5.3)	10
2.3.6 TC6 Transmitted power : PP and RFP with internal antenna(4.5.4.1.1)	14
2.3.7 TC7 Transmitted power :PPand RFP with an external ant. Connector(4.5.4.1.2)	14
2.3.8 TC8 RF-carrier modulation(4.5.5)	15
2.3.9 TC9 Emissions due to modulation(4.5.6.2)	15
2.3.10 TC10 Emissions due to transmitter transients(4.5.6.3)	16
2.3.11 TC11 Emissions due to intermodulation(4.5.6.4)	19
2.3.12 TC12 Spurious emissions when allocated a transmit channel(4.5.6.5)	19
2.3.13 TC13 Radio receiver sensitivity(4.5.7.1)	20
2.3.14 TC14 Radio receiver reference bit error ratio(4.5.7.2)	20
2.3.15 TC15 Receiver interference performance(4.5.7.3)	21
2.3.16 TC16 Radio receiver blocking, case1(4.5.7.4)	22
2.3.17 TC17 Radio receiver blocking, case2(4.5.7.5)	23
2.3.18 TC18 Receiver intermodulation performance(4.5.7.6)	23
2.3.19 TC19 Spurious emissions when the radio endpoint has no allocated transmit ch.(4.5.7.7)	24
2.3.20 TC20 Synchronisation port(4.5.8)	24
2.3.21 TC21 Equipment identity verification/safeguards(4.5.9)	24
2.3.22 TC22 Efficient use of radio spectrum(4.5.10)	24
2.3.23 TC23 WRS(4.5.11)	24
2.3.24 TC24 PP to PP communication	24
2.3.25 TC25 Direct communication	24
2.3.26 TC26 Higher level modulation	24

### **3 Annex**

<b>4 Appendix</b> Photo of the Test Candidate	25
---	----

## 1.1 Reason for measurements and identification of the protocol

The Test Candidate shall be tested to

DECT, General terminal attachment requirements

EN 301 406	V1.5.1 (2003-07)
EN 300 175-2, PHL	July 2003

### 1.1.1 Global statement of conformance

Has the applicant filled out the Client Test Preparation Information in accordance to EN301 406	<b>Yes</b>
--	------------

see annex EN301 406 Statement of the applicant“

## 1.2 Identification and functional description of the test candidate

### 1.2.1 Client identification

Name	SunCorp Communications Limited
Contact person	Mr. C.W. Cheung
Address	Room 1907-08, Harcourt House, 39 Gloucester Road, Wanchai, Hong Kong
Phone No.	86 755 25733333/ 25736666
Fax No.	86 755 5732288

### 1.2.2 Identification of the Test Candidate:

RFPI of the FP with int. antenna	- -
RFPI of the FP with temp. ant. con.	1122330100
Hardware version	- -
Software version	- -
Operating voltage nom/min/max	230VAC/207VAC/253VAC
Serial No of the FP with int. antenna.	- -
Serial No of the FP with temp. ant. con.	- -

### 1.2.3 Functional description

The Test Candidate is a fixed part with integrated antennas of a cordless telephone system for 3.1 kHz voice-communications on **DECT-standard**. For the integrated antennas a diversity-switch is included to the equipment. This fixed part(FP)is used in combination with a portable part (PP) for connections to the analogue public switched telephone network

For the tests one sample with integrated antenna and one sample with 50  $\Omega$ -connector were available to the test lab.

### 1.3 Climatic Conditions

Temperature °C	Rel. Humidity %	Atmospheric Pressure
nominal value		
aimed +15°C - +35°C	aimed 20% - 75%	aimed 86 - 106 kPa

The requirements for temperature, rel. humidity and atmospheric pressure were observed and be within the specified range.

### 1.4 Measurement accuracy

The measurement accuracy is in accordance with EN301 406 V1.5.1 (2003-07).

Note: All values reflect a confidence level of 95 %.

The actual measurement uncertainties are described at each test.

### 1.5 Test equipment used

Equipment	Inventory-No.:
R&S DECT Type approval system TS 8930 FTAS:	
Process Controller	H1882000176
R&S Signalling unit TS1220	-
RF-Generator	H1882000179
RF-Generator	H1882000187
Spectrum- Analyzer	H1882000186
Switch Matrix	H1882000185
RF-Generator	H1882000162
Software	DOS-Version 3.02F from 19.02.99
Anechoic Chamber V	
Spectrum- Analyzer	H1882000161
RF-Pre-Amplifier	H1882000169
RF-Pre-Amplifier	H1882000170
RF-Filter	H1882000189
RF-Filter	H1882000190
RF-Antenna	H1882000145
RF-Antenna	H1882000146
RF-Antenna	H1882001604
RF-Antenna	H1882001605
Control-PC	H1882000140
Software T_Case_12	V 3.1 from 19.07.99

### 1.6 Explanation of the results abbreviations

P = pass, inside of the specification

P\* = pass, inside of the specification in consideration of the test accuracy

F = failed, exceeding the specification

O = not implicated

- = not tested

? = no clear result considering to the specification

\* = see note

## 1.7 Comments for testing

Delivery date of Test Candidate: 2008.01.14  
The tests were done from 2008.01.14 at 2008.02.05

### Test Location T01

During the tests were present:  
Mr. Jeff Pong from **TÜV SÜD Hong Kong Ltd.**  
Mr. C.W. Cheung from **SunCorp Communications Limited**

The test set-up and tests are according to EN301 406 V1.5.1(2003-07) and **DTAAB DT.04 V10 from 11/99** and the internal test comments of the test lab.

All measurements, in exception of parts of Testcase 6 and Testcase 12, were done at the equipment with 50  $\Omega$ -temporary antenna connector.

All radiated measurements were done in the anechoic chamber  
The test site and the whole test equipment is according to standards  
EN301 406 V1.5.1 (2003-07).

## 2 IUT conformance status according to EN301 406 V1.5.1(2003-07)

### 2.1 IUT conformance summary

The IUT **has not been** shown by conformance assessment to be non conforming to the general terminal attachment requirements, EN301 406

### 2.2 EN301 406 results overview

Test case	Point	Testcase description	Remarks	Sel.	Run	Verdict
1	4.5.1	Accuracy and stability of RF carriers		Y	Y	Pass
2	4.5.2	Timing jitter: slot - slot on the same channel		Y	Y	Pass
3		Reference timing accuracy of a RFP		Y	Y	Pass
4		Measurement of packet timing accuracy	only for portable part	N	N	----
5	4.5.3	Transmission burst		Y	Y	Pass
6	4.5.4.1.1	Transmitted power (with an internal antenna) NTP		Y	Y	Pass
7	4.5.4.1.2	Transmitted power (with an external antenna connector)		Y	Y	Pass
8	4.5.5	RF carrier modulation		Y	Y	Pass
9	4.5.6.2	Emissions due to modulation		Y	Y	Pass
10	4.5.6.3	Emissions due to transmitter transients		Y	Y	Pass
11	4.5.6.4	Emissions due to intermodulation	only for basestation with more than one transmitter	N	N	---
12	4.5.6.5	Spurious emissions when allocated a transmit channel	Conducted spurious	Y	Y	Pass
			Radiated spurious			Pass
13	4.5.7.1	Radio receiver sensitivity		Y	Y	Pass
14	4.5.7.2	Radio receiver reference bit error ratio		Y	Y	Pass
15	4.5.7.3	Radio receiver interference performance		Y	Y	Pass
16	4.5.7.4	Radio receiver blocking case 1		Y	Y	Pass
17	4.5.7.5	Radio receiver blocking case 2		Y	Y	Pass
18	4.5.7.6	Receiver intermodulation performance		Y	Y	Pass
19	4.5.7.7	Spurious emissions when the radio endpoint has no allocated transmit channel	only for portable part	N	N	---

*EN301 406 V1.5.1(2003-07) results overview*

Test case	Point	Testcase description	Remarks	Sel.	Verdict
20	4.5.8	Synchronisation port		N	<b>No test</b>
21	4.5.9	Equipment identity verification /safeguards		N	<b>Manufacturer declaration</b>
22	4.5.10	Efficient use of radio spectrum		N	<b>Manufacturer declaration</b>
23	4.5.11	WRS		N	<b>No test</b>
24	4.5.12	PP to PP communication		N	<b>No test</b>
25	4.5.13	Direct communication		N	<b>No test</b>
26	4.5.14	Higher level modulation		N	<b>No test</b>



## 2.3 Test campaign report

### 2.3.1 TC 1 Accuracy and stability of RF carriers (4.5.1)

aimed for  $t \geq 1$  s with  $\Delta f \leq \pm 50$  kHz under nominal and extreme conditions

	Deviation [kHz]		
	channel 0	channel 5	Channel 9
nom. temperature and nom. Voltage	<b>-1.57</b>	<b>-1.95</b>	<b>-1.72</b>
+10°C and minimum voltage	<b>-5.42</b>	<b>-5.73</b>	<b>-5.48</b>
+10°C and maximum voltage	<b>-5.53</b>	<b>-5.68</b>	<b>-5.45</b>
+40°C and minimum voltage	<b>0.77</b>	<b>0.70</b>	<b>1.24</b>
+40°C and maximum voltage	<b>0.81</b>	<b>0.99</b>	<b>0.87</b>

Measurement uncertainty: < 1%

Comment: minimum voltage = 207V

P  
P  
P  
P  
P

### 2.3.2 TC 2 Timing jitter: slot- slot on the same channel (4.5.2)

Test in channel 5 aimed $< \pm 1$ $\mu$ s	Deviation [ $\mu$ s]	
	positive	Negative
nom. temperature and nom. Voltage	<b>0.064</b>	<b>-0.075</b>
+10°C and minimum voltage	<b>0.048</b>	<b>-0.059</b>
+10°C and maximum voltage	<b>0.045</b>	<b>-0.065</b>
+40°C and minimum voltage	<b>0.058</b>	<b>-0.069</b>
+40°C and maximum voltage	<b>0.059</b>	<b>-0.095</b>

Measurement uncertainty:  $\leq 77.4$  ns

Comment: minimum voltage = 207V

P  
P  
P  
P  
P

### 2.3.3 TC 3 Reference timing accuracy of a RFP

Test in channel 5	Aimed	Deviation [ppm]
nom. temperature and nom. Voltage	< 5 ppm	<b>-0.56</b>
+10°C and minimum voltage	< 10 ppm	<b>-0.87</b>
+10°C and maximum voltage	< 10 ppm	<b>-0.87</b>
+40°C and minimum voltage	< 10 ppm	<b>-0.98</b>
+40°C and maximum voltage	< 10 ppm	<b>-0.99</b>

Measurement uncertainty:  $\leq 77.4$  ns

Comment: minimum voltage = 207V


P  
P  
P  
P  
P

### 2.3.4 TC 4 Measurement of packet timing accuracy

*only recommended for portable parts*


2.3.5 TC 5 Transmission Burst (4.5.3)

Measurement uncertainty: + 0.85 dB / -0.92 dB




Nom. temperature and nom. Voltage

P




Nom. temperature and nom. voltage

P




Nom. temperature and nom. voltage

P




+10°C temperature and nom. Voltage

P




+10°C temperature and nom. voltage

P




+10°C temperature and nom. voltage

P




+40°C temperature and nom. voltage

P



+40°C temperature and nom. voltage

P



+40°C temperature and nom. voltage

P

### 2.3.6 TC 6 Transmitted power: PP and FP with internal antenna (4.5.4.1.1)

Conducted RF-output power in the Burst:

aimed  $\leq 250$  mW (24 dBm)

Height of receive antenna

actual = **1.50 m**

Radiated field strength maximum at position in degrees

ant. 0 actual = **10°** hor

ant. 1 actual = **230°** ver

Antenna gain: aimed with max. 12 dB

Antenna 0	conducted Power	radiated Power	Antenna gain
Channel 0	22.80 dBm	20.10 dBm	-2.70 dB
Channel 5	23.20 dBm	20.51 dBm	-2.70 dB
Channel 9	23.40 dBm	20.95 dBm	-2.45 dB

P

Measurement uncertainty radiated: + 3.53 dB / -3.53 dB

Measurement uncertainty conducted: + 0.85 dB / -0.92 dB

### 2.3.7 TC 7 Transmitted power: FP with an external ant. connector (4.5.4.1.2)

not applicable

### 2.3.8

#### TC 8 RF-carrier modulation (4.5.5)

part 1: aimed  $> \pm 259 \text{ kHz} < \pm 403 \text{ kHz}$   
 part 2-3: aimed  $> \pm 202 \text{ kHz} < \pm 403 \text{ kHz}$   
 part 4: aimed  $< \pm 15 \text{ kHz/slot}$

Measurement uncertainty part 1-3:  $\pm 10 \text{ kHz}$   
 part 4:  $\pm 2 \text{ kHz}$

TRAFFIC SLOT: 6

TRAFFIC CARRIER: 5

PACKET TYPE: P32+Z

part1: 10 bursts evaluated

maximum positive modulation: 389.86 kHz

maximum negative modulation: -369.28 kHz

part2: 10 bursts evaluated

maximum positive modulation: 371.01 kHz

maximum negative modulation: -338.54 kHz

part3: 10 bursts evaluated

maximum positive modulation: 340.42 kHz

maximum negative modulation: -337.00 kHz

part4: 200 bursts evaluated

averaged frequency drift: -5.35kHz/slot

P  
P  
  
P  
P  
  
P  
P  
  
P

### 2.3.9

#### TC 9 Emissions due to modulation (4.5.6.2)

Measurement uncertainty:  $+ 0.49 \text{ dB} / -0.51 \text{ dB}$

One exception  $< -33 \text{ dBm}$  (500 nW) permissible

TRAFFIC SLOT: 0

TRAFFIC CARRIER: 0

PACKET TYPE: P32+Z

measured NTP: 22.90 dBm

		measured values	limits	
CARRIER 0:	integrated power	22.90 dBm	---	P
CARRIER 1:	integrated power	-16.54 dBm	-8 dBm	P
CARRIER 2:	integrated power	-38.81 dBm	-30 dBm	P
CARRIER 3:	integrated power	-46.61 dBm	-41 dBm	P
CARRIER 4:	integrated power	-48.87 dBm	-44 dBm	P
CARRIER 5:	integrated power	-49.89 dBm	-44 dBm	P
CARRIER 6:	integrated power	-50.50 dBm	-44 dBm	P
CARRIER 7:	integrated power	-50.75 dBm	-44 dBm	P
CARRIER 8:	integrated power	-50.34 dBm	-44 dBm	P
CARRIER 9:	integrated power	-51.19 dBm	-44 dBm	P



TRAFFIC SLOT:	2			
TRAFFIC CARRIER:	5			
PACKET TYPE:	P32+Z			
measured NTP:	23.30 dBm			
		measured values	limits	
CARRIER 0:	integrated power	- 49.8 dBm	-44 dBm	P
		9		
CARRIER 1:	integrated power	- 48.8 dBm	-44 dBm	P
		8		
CARRIER 2:	integrated power	- 46.3 dBm	-41 dBm	P
		3		
CARRIER 3:	integrated power	- 41.0 dBm	-30 dBm	P
		1		
CARRIER 4:	integrated power	- 19.0 dBm	-8 dBm	P
		3		
CARRIER 5:	integrated power	23.3 dBm	---	P
		0		
CARRIER 6:	integrated power	- 16.9 dBm	-8 dBm	P
		4		
CARRIER 7:	integrated power	- 38.2 dBm	-30 dBm	P
		6		
CARRIER 8:	integrated power	- 46.3 dBm	-41 dBm	P
		4		
CARRIER 9:	integrated power	- 48.5 dBm	-44 dBm	P
		7		

TRAFFIC SLOT:	8			
TRAFFIC CARRIER:	9			
PACKET TYPE:	P32+Z			
measured NTP:	23.50 dBm			
		measured values	limits	
CARRIER 0:	integrated power	- 50.5 dBm	-44 dBm	P
		3		
CARRIER 1:	integrated power	- 50.1 dBm	-44 dBm	P
		8		
CARRIER 2:	integrated power	- 50.2 dBm	-44 dBm	P
		5		
CARRIER 3:	integrated power	- 49.9 dBm	-44 dBm	P
		2		
CARRIER 4:	integrated power	- 49.4 dBm	-44 dBm	P
		0		
CARRIER 5:	integrated power	- 47.1 dBm	-44 dBm	P
		0		
CARRIER 6:	integrated power	- 45.6 dBm	-41 dBm	P
		6		
CARRIER 7:	integrated power	- 40.3 dBm	-30 dBm	P
		7		
CARRIER 8:	integrated power	- 18.4 dBm	-8 dBm	P
		1		
CARRIER 9:	integrated power	23.5 dBm	---	P
		0		

#### 2.3.10 TC 10 Emissions due to transmitter transients (4.5.6.3)

Measurement uncertainty: + 0.49 dB / -0.51 dB



TRAFFIC SLOT: 10  
 TRAFFIC CARRIER: 0  
 PACKET TYPE: P32+Z

		measured values		limits	
CARRIER 0:	max. Power	190.05 mW	( 22.79 dBm)	---	p
CARRIER 1:	max. Power	167.11 uW	( -7.77 dBm)	-6 dBm	p
CARRIER 2:	max. Power	273.73 nW	( -35.63 dBm)	-14 dBm	p
CARRIER 3:	max. Power	42.39 nW	( -43.73 dBm)	-24 dBm	p
CARRIER 4:	max. Power	125.77 nW	( -39.00 dBm)	-30 dBm	p
CARRIER 5:	max. Power	15.33 nW	( -48.15 dBm)	-30 dBm	p
CARRIER 6:	max. Power	18.26 nW	( -47.38 dBm)	-30 dBm	p
CARRIER 7:	max. Power	11.51 nW	( -49.39 dBm)	-30 dBm	p
CARRIER 8:	max. Power	111.24 nW	( -39.54 dBm)	-30 dBm	p
CARRIER 9:	max. Power	10.12 nW	( -49.95 dBm)	-30 dBm	p

TRAFFIC SLOT: 2  
 TRAFFIC CARRIER: 1  
 PACKET TYPE: P32+Z

		measured values		limits	
CARRIER 0:	max. Power	141.05 uW	( -8.51 dBm)	-6 dBm	p
CARRIER 1:	max. Power	178.21 mW	( 22.51 dBm)	---	p
CARRIER 2:	max. Power	184.57 uW	( -7.34 dBm)	-6 dBm	p
CARRIER 3:	max. Power	339.85 nW	( -34.69 dBm)	-14 dBm	p
CARRIER 4:	max. Power	32.58 nW	( -44.87 dBm)	-24 dBm	p
CARRIER 5:	max. Power	130.26 nW	( -38.85 dBm)	-30 dBm	p
CARRIER 6:	max. Power	17.13 nW	( -47.66 dBm)	-30 dBm	p
CARRIER 7:	max. Power	18.16 nW	( -47.41 dBm)	-30 dBm	p
CARRIER 8:	max. Power	10.06 nW	( -49.97 dBm)	-30 dBm	p
CARRIER 9:	max. Power	117.94 nW	( -39.28 dBm)	-30 dBm	p

TRAFFIC SLOT: 4  
 TRAFFIC CARRIER: 2  
 PACKET TYPE: P32+Z

		measured values		limits	
CARRIER 0:	max. Power	273.73 nW	( -35.63 dBm)	-14 dBm	p
CARRIER 1:	max. Power	138.59 uW	( -8.58 dBm)	-6 dBm	p
CARRIER 2:	max. Power	203.86 mW	( 23.09 dBm)	---	p
CARRIER 3:	max. Power	146.08 uW	( -8.35 dBm)	-6 dBm	p
CARRIER 4:	max. Power	298.82 nW	( -35.25 dBm)	-14 dBm	p
CARRIER 5:	max. Power	41.41 nW	( -43.83 dBm)	-24 dBm	p
CARRIER 6:	max. Power	134.92 nW	( -38.70 dBm)	-30 dBm	p
CARRIER 7:	max. Power	14.97 nW	( -48.25 dBm)	-30 dBm	p
CARRIER 8:	max. Power	23.49 nW	( -46.29 dBm)	-30 dBm	p
CARRIER 9:	max. Power	11.05 nW	( -49.57 dBm)	-30 dBm	p

TRAFFIC SLOT: 6  
 TRAFFIC CARRIER: 3  
 PACKET TYPE: P32+Z

		measured values		limits	
CARRIER 0:	max. Power	37.93 nW	( -44.21 dBm)	-24 dBm	p
CARRIER 1:	max. Power	371.00 nW	( -34.31 dBm)	-14 dBm	p
CARRIER 2:	max. Power	138.59 uW	( -8.58 dBm)	-6 dBm	p
CARRIER 3:	max. Power	194.55 mW	( 22.89 dBm)	---	p
CARRIER 4:	max. Power	156.70 uW	( -8.05 dBm)	-6 dBm	p

CARRIER 5:	max. Power	362.42 nW	( -34.41 dBm)	-14 dBm	p
CARRIER 6:	max. Power	46.28 nW	( -43.35 dBm)	-24 dBm	p
CARRIER 7:	max. Power	142.21 nW	( -38.47 dBm)	-30 dBm	p
CARRIER 8:	max. Power	16.54 nW	( -47.82 dBm)	-30 dBm	p
CARRIER 9:	max. Power	17.84 nW	( -47.49 dBm)	-30 dBm	p

TRAFFIC SLOT: 8  
 TRAFFIC CARRIER: 4  
 PACKET TYPE: P32+Z

		measured values	limits		
CARRIER 0:	max. Power	117.25 nW	( -39.31 dBm)	-30 dBm	P
CARRIER 1:	max. Power	32.97 nW	( -44.82 dBm)	-24 dBm	p
CARRIER 2:	max. Power	405.01 nW	( -33.93 dBm)	-14 dBm	p
CARRIER 3:	max. Power	132.26 uW	( -8.79 dBm)	-6 dBm	p
CARRIER 4:	max. Power	206.26 mW	( 23.14 dBm)	---	p
CARRIER 5:	max. Power	170.07 uW	( -7.69 dBm)	-6 dBm	p
CARRIER 6:	max. Power	311.31 nW	( -35.07 dBm)	-14 dBm	p
CARRIER 7:	max. Power	50.22 nW	( -42.99 dBm)	-24 dBm	p
CARRIER 8:	max. Power	128.75 nW	( -38.90 dBm)	-30 dBm	p
CARRIER 9:	max. Power	15.15 nW	( -48.20 dBm)	-30 dBm	p

TRAFFIC SLOT: 0  
 TRAFFIC CARRIER: 5  
 PACKET TYPE: P32+Z

		measured values	limits		
CARRIER 0:	max. Power	13.88 nW	( -48.58 dBm)	-30 dBm	p
CARRIER 1:	max. Power	121.44 nW	( -39.16 dBm)	-30 dBm	p
CARRIER 2:	max. Power	34.95 nW	( -44.57 dBm)	-24 dBm	p
CARRIER 3:	max. Power	356.12 nW	( -34.48 dBm)	-14 dBm	p
CARRIER 4:	max. Power	146.08 uW	( -8.35 dBm)	-6 dBm	p
CARRIER 5:	max. Power	176.14 mW	( 22.46 dBm)	---	p
CARRIER 6:	max. Power	153.08 uW	( -8.15 dBm)	-6 dBm	p
CARRIER 7:	max. Power	393.34 nW	( -34.05 dBm)	-14 dBm	p
CARRIER 8:	max. Power	33.55 nW	( -44.74 dBm)	-24 dBm	p
CARRIER 9:	max. Power	128.75 nW	( -38.90 dBm)	-30 dBm	p

TRAFFIC SLOT: 2  
 TRAFFIC CARRIER: 6  
 PACKET TYPE: P32+Z

		measured values	limits		
CARRIER 0:	max. Power	17.03 nW	( -47.69 dBm)	-30 dBm	p
CARRIER 1:	max. Power	12.86 nW	( -48.91 dBm)	-30 dBm	p
CARRIER 2:	max. Power	106.16 nW	( -39.74 dBm)	-30 dBm	p
CARRIER 3:	max. Power	34.34 nW	( -44.64 dBm)	-24 dBm	p
CARRIER 4:	max. Power	463.31 nW	( -33.34 dBm)	-14 dBm	p
CARRIER 5:	max. Power	145.23 uW	( -8.38 dBm)	-6 dBm	p
CARRIER 6:	max. Power	201.49 mW	( 23.04 dBm)	---	p
CARRIER 7:	max. Power	183.50 uW	( -7.36 dBm)	-6 dBm	p
CARRIER 8:	max. Power	391.04 nW	( -34.08 dBm)	-14 dBm	p
CARRIER 9:	max. Power	39.75 nW	( -44.01 dBm)	-24 dBm	p

TRAFFIC SLOT: 4  
 TRAFFIC CARRIER: 7  
 PACKET TYPE: P32+Z

		measured values	limits		
CARRIER 0:	max. Power	9.77 nW	( -50.10 dBm)	-30 dBm	p
CARRIER 1:	max. Power	15.78 nW	( -48.02 dBm)	-30 dBm	p
CARRIER 2:	max. Power	12.20 nW	( -49.14 dBm)	-30 dBm	p
CARRIER 3:	max. Power	134.13 nW	( -38.72 dBm)	-30 dBm	p
CARRIER 4:	max. Power	35.16 nW	( -44.54 dBm)	-24 dBm	p

CARRIER 5:	max. Power	330.05 nW	( -34.81 dBm)	-14 dBm	p
CARRIER 6:	max. Power	143.54 uW	( -8.43 dBm)	-6 dBm	p
CARRIER 7:	max. Power	202.68 mW	( 23.07 dBm)	---	p
CARRIER 8:	max. Power	179.26 uW	( -7.47 dBm)	-6 dBm	p
CARRIER 9:	max. Power	333.94 nW	( -34.76 dBm)	-14 dBm	p

TRAFFIC SLOT: 6  
 TRAFFIC CARRIER: 8  
 PACKET TYPE: P32+Z

		measured values		limits	
CARRIER 0:	max. Power	96.11 nW	( -40.17 dBm)	-30 dBm	p
CARRIER 1:	max. Power	10.60 nW	( -49.75 dBm)	-30 dBm	p
CARRIER 2:	max. Power	15.97 nW	( -47.97 dBm)	-30 dBm	p
CARRIER 3:	max. Power	12.56 nW	( -49.01 dBm)	-30 dBm	p
CARRIER 4:	max. Power	116.57 nW	( -39.33 dBm)	-30 dBm	p
CARRIER 5:	max. Power	41.41 nW	( -43.83 dBm)	-24 dBm	p
CARRIER 6:	max. Power	293.63 nW	( -35.32 dBm)	-14 dBm	p
CARRIER 7:	max. Power	146.94 uW	( -8.33 dBm)	-6 dBm	p
CARRIER 8:	max. Power	200.32 mW	( 23.02 dBm)	---	p
CARRIER 9:	max. Power	184.57 uW	( -7.34 dBm)	-6 dBm	p

TRAFFIC SLOT: 8  
 TRAFFIC CARRIER: 9  
 PACKET TYPE: P32+Z

		measured values		limits	
CARRIER 0:	max. Power	10.06 nW	( -49.97 dBm)	-30 dBm	p
CARRIER 1:	max. Power	97.24 nW	( -40.12 dBm)	-30 dBm	p
CARRIER 2:	max. Power	11.99 nW	( -49.21 dBm)	-30 dBm	p
CARRIER 3:	max. Power	14.54 nW	( -48.37 dBm)	-30 dBm	p
CARRIER 4:	max. Power	18.16 nW	( -47.41 dBm)	-30 dBm	p
CARRIER 5:	max. Power	119.33 nW	( -39.23 dBm)	-30 dBm	p
CARRIER 6:	max. Power	30.91 nW	( -45.10 dBm)	-24 dBm	p
CARRIER 7:	max. Power	314.97 nW	( -35.02 dBm)	-14 dBm	p
CARRIER 8:	max. Power	103.46 uW	( -9.85 dBm)	-6 dBm	p
CARRIER 9:	max. Power	196.84 mW	( 22.94 dBm)	---	p

### 2.3.11 TC 11 Emissions due to intermodulation (4.5.6.4)

*only for basestations with several transmitters*

### 2.3.12 TC 12 Spurious emissions when allocated a transmit channel (4e.5.6.5)

Channel 5, radiated

30 MHz - 1 GHz	aimed ≤ -36 dBm	actual ≤ -57.15 dBm	p
1 GHz - 4 GHz	aimed ≤ -30 dBm	actual ≤ -45.75 dBm	p
Peak at 3.777 GHz hor.	aimed ≤ -30 dBm	actual ≤ -37.69 dBm	p
broadcast bands according to TBR 6	aimed ≤ -47 dBm	actual ≤ -71.65 dBm	p
Measurement uncertainty f<1GHz: + 2.89 dB / -2.98 dB			
f>1GHz: + 3.40 dB / -3.75 dB			

Channel 5, conducted

TRAFFIC SLOT: 2  
TRAFFIC CARRIER: 5  
PACKET TYPE: P32+Z  
Wideband Measurements  
Range from 300kHz to 12750.00 MHz  
Measurement uncertainty f>1GHz: + 1.40 dB / -1.75 dB

P

### 2.3.13 TC 13 Radio receiver sensitivity (4.5.7.1)

At a level of -83 dBm the BER shall be  $\leq 10^{-3}$ .  
Measurement uncertainty: + 0.25 dB / -0.27 dB

TRAFFIC SLOT:	2			
TRAFFIC CARRIER:	0			
PACKET TYPE:	P32+Z			
Center frequency offset:	0 kHz			
BER: 0.00000000	FER: 0.000000	evaluated:	320 kbit	P
Center frequency offset:	50 kHz			
BER: 0.00000000	FER: 0.000000	evaluated:	320 kbit	P
Center frequency offset:	-50 kHz			
BER: 0.00000000	FER: 0.000000	evaluated:	320 kbit	P
TRAFFIC SLOT:	4			
TRAFFIC CARRIER:	5			
PACKET TYPE:	P32+Z			
Center frequency offset:	0 kHz			
BER: 0.00000000	FER: 0.000000	evaluated:	320 kbit	P
Center frequency offset:	50 kHz			
BER: 0.00000000	FER: 0.000000	evaluated:	320 kbit	P
Center frequency offset:	-50 kHz			
BER: 0.00000000	FER: 0.000000	evaluated:	320 kbit	P
TRAFFIC SLOT:	8			
TRAFFIC CARRIER:	9			
PACKET TYPE:	P32+Z			
Center frequency offset:	0 kHz			
BER: 0.00000000	FER: 0.000000	evaluated:	320 kbit	P
Center frequency offset:	50 kHz			
BER: 0.00000000	FER: 0.000000	evaluated:	320 kbit	P
Center frequency offset:	-50 kHz			
BER: 0.00000000	FER: 0.000000	evaluated:	320 kbit	P

### 2.3.14 TC 14 Radio receiver reference bit error ratio (4.5.7.2)

At a level of -73 dBm the BER shall be  $\leq 10^{-5}$ , the FER shall be  $\leq 5 \cdot 10^{-4}$ .  
Measurement uncertainty: + 0.25 dB

TRAFFIC SLOT:	0			
TRAFFIC CARRIER:	0			
PACKET TYPE:	P32+Z			
BER: 0.00000307	FER: 0.000000	evaluated:	95.043 Mbit	P
TRAFFIC SLOT:	2			
TRAFFIC CARRIER:	5			
PACKET TYPE:	P32+Z			
BER: 0.00000366	FER: 0.000000	evaluated:	77.084 Mbit	P
TRAFFIC SLOT:	4			
TRAFFIC CARRIER:	9			
PACKET TYPE:	P32+Z			
BER: 0.00000255	FER: 0.000000	evaluated:	77.440 Mbit	P

### 2.3.15 TC 15 Radio receiver interference performance (4.5.7.3)

The BER shall be  $\leq 10^{-3}$ .

Measurement uncertainty: + 0.32 dB / -0.34 dB

TRAFFIC SLOT: 8  
TRAFFIC CARRIER: 0  
PACKET TYPE: P32+Z  
BER: FER: kBit: intf.car: lev in dBm:  
0.000020 0.000000 351 -3 -33.0  
0.000003 0.000000 326 -2 -39.0  
0.000009 0.000000 338 -1 -60.0  
0.000304 0.000000 809 0 -84.0  
0.000000 0.000000 320 1 -60.0  
0.000003 0.000000 326 2 -39.0  
0.000000 0.000000 320 3 -33.0  
0.000000 0.000000 320 4 -33.0  
0.000000 0.000000 320 5 -33.0  
0.000000 0.000000 320 6 -33.0  
0.000000 0.000000 320 7 -33.0  
0.000000 0.000000 320 8 -33.0  
0.000000 0.000000 320 9 -33.0  
0.000000 0.000000 320 10 -33.0  
0.000000 0.000000 320 11 -33.0  
0.000000 0.000000 320 12 -33.0

TRAFFIC SLOT: 10  
TRAFFIC CARRIER: 5  
PACKET TYPE: P32+Z  
BER: FER: kBit: intf.car: lev in dBm:  
0.000000 0.000000 320 -3 -33.0  
0.000003 0.000000 326 -2 -33.0  
0.000000 0.000000 320 -1 -33.0  
0.000006 0.000000 332 0 -33.0  
0.000000 0.000000 320 1 -33.0  
0.000003 0.000000 326 2 -33.0  
0.000003 0.000000 326 3 -39.0  
0.000000 0.000000 320 4 -60.0  
0.000364 0.000000 950 5 -84.0  
0.000000 0.000000 320 6 -60.0  
0.000000 0.000000 320 7 -39.0  
0.000003 0.000000 326 8 -33.0  
0.000000 0.000000 320 9 -33.0  
0.000003 0.000000 326 10 -33.0  
0.000000 0.000000 320 11 -33.0  
0.000000 0.000000 320 12 -33.0

P  
P  
P  
P  
P  
P  
P  
P  
P  
P  
P  
P  
P  
P  
P  
P  
P  
P  
P  
P

P  
P  
P  
P  
P  
P  
P  
P  
P  
P  
P  
P  
P  
P  
P  
P  
P  
P  
P  
P

P  
P  
P  
P  
P  
P  
P  
P  
P  
P  
P  
P  
P  
P  
P

The BER shall be  $\leq 10^{-3}$ .

Measurement uncertainty: + 3.00 dB / -3.00 dB radiated

P

P

P

### 2.3.17 TC 17 Radio receiver blocking, case 2 (4.5.7.5)

The BER shall be  $\leq 10^{-3}$ .

Measurement uncertainty: + 0.63 dB / -0.71 dB

TRAFFIC SLOT: 8  
TRAFFIC CARRIER: 0  
PACKET TYPE: P32+Z  
BER: 0.00000000 FER: 0.000000 evaluated: 320 kbit

P

TRAFFIC SLOT: 2  
TRAFFIC CARRIER: 5  
PACKET TYPE: P32+Z  
BER: 0.00000000 FER: 0.000000 evaluated: 320 kbit

P

TRAFFIC SLOT: 4  
TRAFFIC CARRIER: 9  
PACKET TYPE: P32+Z  
BER: 0.00000000 FER: 0.000000 evaluated: 320 kbit

P

### 2.3.18 TC 18 Receiver intermodulation performance (4.5.7.6)

The BER shall be  $\leq 10^{-3}$ .

Measurement uncertainty: + 0.40 dB / -0.43 dB

TRAFFIC SLOT: 6  
TRAFFIC CARRIER: 0  
PACKET TYPE: P32+Z  
M: 0 A: 2 B: 4  
BER: 0.000000 FER: 0.0000 eval.data: 320 kbit  
M: 0 A: -2 B: -4  
BER: 0.000012 FER: 0.0000 eval.data: 345 kbit

P

P

TRAFFIC SLOT: 10  
TRAFFIC CARRIER: 5  
PACKET TYPE: P32+Z  
M: 5 A: 7 B: 9  
BER: 0.000000 FER: 0.0000 eval.data: 320 kbit  
M: 5 A: 3 B: 1  
BER: 0.000000 FER: 0.0000 eval.data: 320 kbit

P

P

TRAFFIC SLOT: 2  
TRAFFIC CARRIER: 9  
PACKET TYPE: P32+Z  
M: 9 A: 11 B: 13  
BER: 0.000000 FER: 0.0000 eval.data: 320 kbit  
M: 9 A: 7 B: 5  
BER: 0.000014 FER: 0.0000 eval.data: 351 kbit

P

P



**2.3.19 TC 19 Spurious emissions when the radio endpoint has no allocated transmit ch. (4.5.7.7)**  
*only recommended for portable parts*

**2.3.20 TC 20 Synchronisation port (4.5.8)**  
No test

**2.3.21 TC 21 Equipment identity verification (4.5.9)**  
Statement of the applicant“

**2.3.22 TC 22 Efficient use of radio spectrum (4.5.10)**  
Statement of the applicant“

**2.3.23 TC23 WRS (4.5.11)**  
No test

**2.3.24 TC24 PP to PP communication (4.5.12)**  
No test

**2.3.25 TC25 Direct communication (4.5.13)**  
No test

**2.3.26 TC26 Higher level modulation (4.5.14)**  
No test



#### 4 Appendix Photo of the Test Candidate (exterior)



Photo of the Test Candidate (exterior)



Photo of the Test Candidate (interior)



# MANUFACTURER DECLARATION

## SunCorp Communications Limited

Room 1907-08, 19/F, Harcourt House, 39 Gloucester Road, Wanchai, Hong Kong

(Name / Address)

declares for the Digital Enhanced Cordless Telecommunications (DECT) telephone system specified as

DECT20-B14-RF19

### The Portable Part (PP):

It is not possible for the user to alter the IPEI using any normally accessible procedure. We supply, in addition to the equipment, sufficient means in the equipment with instructions in the documentation to permit validation of the Equipment Manufacturer's Code and verification of the existence of the Portable equipment Serial Number (PSN) code in the equipment.

### The Fixed Part (FP):

DECT FPs which do not transmit the TA escape message transmits the Nr message as defined in EN 300 175-3 [3] at least once every 10 seconds on all active physical channels;  
These Nr identity messages are transmitted with the appropriate A-field header code as defined in EN 300 175-3[3] and the Nr message contains an ETSI distributed code as defined in EN 300 175-6[6].

(Date) 2008-3-13

(Printed full Name) CW Cheung

For and on behalf of  
**SunCorp Communications Limited**  
新 確 通 訊 有 限 公 司

  
Authorized Signature(s)

(Authorized Signature & Company Chop)

**BABT**

# MANUFACTURER DECLARATION

## SunCorp Communications Limited

Room 1907-08, 19/F, Harcourt House, 39 Gloucester Road, Wanchai, Hong Kong

(Name / Address)

declare for the Digital Enhanced Cordless Telecommunications (DECT) telephone system specified as

DECT20-B14-RF19

(Model Number)

For the portable radio termination (PT):

The first PT transmission on the newly selected channel is made in accordance with the scan sequence of the addressed RFP.

To continue transmitting on the newly selected physical channel the PT transmissions within 2 frames of the first PT transmission.

For the fixed radio termination (FT):

The RFP do not transmit on more than 2 physical channels for which complementary physical channels do not exist.

A complementary physical channel is a physical channel between the same two radio endpoints which occurs 5 ms before or after the physical channel to which is complementary.

When an FT is addressing a specific PT then the first FT transmission is made in accordance with the scan sequence of the addressed PT receiver.

To continue transmitting on the selected physical channel the FT receives an indication that the PT is receiving the FT transmissions within 2 frames of the first FT transmission.

For the channel release:

A REP cease transmission on all physical channels if it has not received a valid indication of the other radio endpoint's identity within 10 seconds of the receipt of the last indication.

A REP which transmits on both the physical channel and complementary physical channel cease to transmit on the channels if either:



The receiving endpoint indicate to the transmitting endpoint that transmission cease on



both these physical channels; or

The transmitting FT or PT is no longer attempting to receive at least one physical channel from the FT or PT to which it is transmitting.

In General:

No more than two physical channels based on the half slot format are sent within the same frame to the same REP;

The EUT is capable of communicating on all 10 DECT RF channels

2008-3-13

(Date)

CW Cheung

(Printed full name)

For and on behalf of  
**SunCorp Communications Limited**

新 雄 通 訊 有 限 公 司

(Authorized signature and company chop)

Authorized Signatures

**BABT**